

ARCA 705030



Sample photo

Order symbol: ARCA 705030
Product nbr: 8120017
Description: Cabinet, PC
Remarks: Grey cover, 2-point locking, hinges on the long side

EAN: 6418074079282
El. number:
 Finland: 3423112
 Electric No. 8212091155
 Denmark:
 Electric No. Sweden: 2500120

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening. Door guide included.

Dimensions:				Accessories:	
mm:	700	500	300	MPP ARCA 7050	Mounting plate perforated
inch:	27.6	19.7	11.8	MPX ARCA 7050	Mounting plate
Materials:				DRS ARCA 705025	DIN rail frame set
Material:	Polycarbonate			DRS ARCA 705030	DIN rail frame set
Base colour:	RAL 7035 -light grey			IDS ARCA 7050	Inner door set
Cover colour:	RAL 7035 -light grey			PMK ARCA 50	Pole mounting kit
Gasket material:	Polyurethane				
Temperatures:				Rating:	
Temperature °C (short term):	-40 ... 120 °C			Ingress Protection (EN 60529): IP66	
Temperature °C (continuous):	-40 ... 80 °C			Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C	
Temperature °F (short term):	-40 ... 250 °F			Electrical insulation: Totally insulated	
Temperature °F (continuous):	-40 ... 175 °F			Halogen free (DIN/VDE 0472, Part 815): 1	
Accessories:				UV resistance: UL 508	
MPS ARCA 7050	Mounting plate			Glow Wire Test (IEC 695-2-1) °C: 960	
				Certificates:	
				SGS Fimko	
				Gost R	

