

RCAS-ES541

Specifications and dimensions



- 22mm Red Mushroom Head Pushbutton
- Key release operation

Features

Diameter	40mm
Depth in front of panel	32mm
Depth behind panel (1 contact)	43mm
Weight	0.11Kg
Available colours	Red
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	10 ⁶ operations
Bezel construction	Bright metal (ZAMAC)

Contact Block

Rated thermal current I _{th}	10A
Rated insulation voltage U _i	500V
Operating force	10N
Operating force additional contacts	5N
Cable capacity	2 x 1.5mm ²
Contact operation	Slow action, positive opening

Related products

Mounting collar (fitted)	RAS-FB
Single hole enclosure	RC-1MY
Single hole enclosure shrouded	RC-1MS
NO contact block	RAS-CBNO
NC contact block	RAS-CBNC
Legend plate	RB2-PY

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440 / Fax: 01582 692 450 e-mail: sales@europacomponents.com
website: <http://www.europacomponents.com>