

## RCAS-ES542

## Specifications and dimensions







•	22mm Red	Mushroom	Head	Push	button
---	----------	----------	------	------	--------

- Twist release operation
- Complete with NC contact

Features				
Diameter	40mm			
Depth in front of panel	32mm			
Depth behind panel (1 contact)	43mm			
Weight	0.11Kg			
Available colours	Red			
Standard	EN 60947-5-1			
Degree of protection	IP65			
Operating temperature	-25°C to +70°C			
Mechanical life	300,000 operations			
Bezel construction	Bright metal (ZAMAC)			
Contact Block				
Rated thermal current Ith	10A			
Rated insulation voltage Ui	500V			
Operating force	8N			
Operating force additional contacts	3N			
Cable capacity	2 x 1.5mm²			
Contact operation	Slow action, positive opening			
Related products				
Mounting collar (fitted)	RAS-FB			
Single hole enclosure	RC-1MY			
Single hole enclosure shrouded	RC-1MS			
NO contact block	RAS-CBNO			
NC contact block	RAS-CBNC			
Legend plate	RB2-PY			

## (i) ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. All products must be installed according to manufacturers instructions.

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440 / Fax: 01582 692 450 e-mail: sales@europacomponents.com website: http://www.europacomponents.com

Page 1 of 1 **EPC**1426-001