

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



RC-4M

Specifications and dimensions

- Four hole empty control station
- Metal enclosure



Features	
Height	164mm
Width	68mm
Depth	51mm
Weight	0.61Kg
Colour	Grey lid on dark grey base
Enclosure construction	Die cast aluminium
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Related Products	
Flush pushbutton	RCAS-PBF
Projecting pushbutton	RCAS-PBP
Booted pushbutton	RCAS-PBB
Selector switch	RCAS-SW
Key switch	RCAS-BG
NO contact block	RAS-BCNO
NC contact block	RAS-BCNC

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**