EUROPA

Data Sheet
EDS2130-001

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation.
All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS

RAS-BCBNC

Specifications and dimensions



- Contact block for 22mm devices
- Designed for use in plastic enclosures
- Normally closed configuration

Features	
Length	30mm
Width	13mm
Depth	24mm
Weight	0.014Kg
Rated thermal current Ith	10A
Rated insulation voltage Ui	500V
Operating force	8N
Cable capacity	2 x 1.5mm^2
Contact operation	Slow action, positive opening
Related Products	
Normally open contact	RAS-BCBNO

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. **All products must be installed according to manufacturers instructions.**

Europa House, Airport Way, Luton, Bedfordshire, LU2 9NH
Technical: 01582 692 444 technical@europa-plc.com
www.europa-plc.com