

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS



RB2-BK125

Specifications and dimensions

- 22mm illuminated selector switch
- 2 position stay put
- Standard lever



Features	
Colour	Amber
Diameter	29mm
Depth in front of panel	22mm
Weight	0.033Kg
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	10 ⁶ operations
Bezel construction	Bright metal (ZAMAC)
Other colours	Red, Green
Related Products	
Mounting collar (available with holder)	RAS-FB
Direct connected lamp holder	RAS-LP6
Diode & series resistor lampholder	RAS-LP7
NO contact block	RAS-CBNO
NC contact block	RAS-CBNC
Legend plate	RB2-PY

ⓘ ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Information provided in data sheets and/or specifications may vary from actual results in different applications and performance may vary over time. All products must be installed according to manufacturers instructions.