EUROPA

Data Sheet
EDS2136-001

This document must be retained for future reference.

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation.
All connections should also be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS

RCAS-ES14

Specifications and dimensions



- 22mm Red Mushroom Head Pushbutton
- Key release operation

Features	
Diameter	40mm
Depth in front of pane	32mm
Depth in front of panel inc key	56mm
Weight	0.04Kg
Available colours	Red
Standard	EN 60947-5-1
Degree of protection	IP65
Operating temperature	-25°C to +70°C
Mechanical life	10^6 operations
Bezel construction	Bright metal (ZAMAC)
Related Products	
Mounting collar (fi tted)	RAS-FB
Single hole enclosure	RC-1MY
Single hole enclosure shrouded	RC-1MS
NO contact block	RAS-CBNO
NC contact block	RAS-CBNC
Legend plate	RB2-PY
Spare key	RB2-K455

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Europa House, Airport Way, Luton, Bedfordshire, LU2 9NH
Technical: 01582 692 444 technical@europa-plc.com
www.europa-plc.com